

	WATER CONNECTION 3/4" GAS
	DRAINING Ø 24mm
	ELECTRICAL SUPPLY

TECHNICAL DATA	STD		UK	
EXTERNAL DIMENSIONS		LS		LS
width	420mm			
depth	490mm			
height	665mm			
WEIGHT	30 kg			
VOLTAGE	230V 50Hz		240V 50Hz	
POWER REQUIRED	2990 W	3200 W	2800 W	3010 W
WATER HARDNESS	2-8 °F			
INLET WATER PRESSURE	200-400 kPa			
CROCKERY DIMENSIONS				
plates diameter	---	280mm	---	280mm
dishes max. height	275mm			
RACK DIMENSION	370X370mm			
RACK EQUIPMENT	2XC10 - 1X10728 - 1X15060			
WASHING CYCLES	1			
WATER SUPPLY 55°C				
racks/h(*) ⁽¹⁾	30			
WATER SUPPLY 10°C				
racks/h(*) ⁽¹⁾	16		14	
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	1.8 L			
BOILER CAPACITY	3 L			
BOILER HEATING ELEMENT	2800 W		2610 W	
RINSING TEMPERATURE (SET)	85°C			
TANK CAPACITY	12.5 L			
TANK HEATING ELEMENT	1850 W			
TANK TEMPERATURE (SET)	55°C			
PUMP POWER	190W<120 L/min***>	400W<185 L/min***>	190W<120 L/min***>	400W<185 L/min***>
DRAIN PUMP (optional)	25 W h MAX draining 0.8m <40***>			
NOISE (dB(A)±0.7)	60.6	61.2	60.6	61.2

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

¹⁾ In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.