



	WATER CONNECTION 3/4" GAS
	DRAIN PIPE Ø 24mm
	ELECTRICAL SUPPLY

TECHNICAL DATA					
EXTERNAL DIMENSIONS					
width		450 mm			
depth		530 mm			
height		720 mm			
WEIGHT(basic version)		45 kg			
VOLTAGE		230V 50Hz			
POWER REQUIRED		3050 W			
WATER HARDNESS		2-8 °F			
INLET WATER PRESSURE		200-400 kPa			
CROCKERY DIMENSIONS					
plates diameter		290 mm			
size allowed		280 mm			
RACK DIMENSIONS		400X400 mm			
RACK EQUIPMENT		2XC121 - 1X10728 - 1X15060			
WASHING CYCLES	(sec)	1 (60)	2 (120)	3 (180)	4 (300)
WATER SUPPLY 55°C					
racks/h(*) <sup>(1)</sup>		43	30	20	12
WATER SUPPLY 10°C					
racks/h(*) <sup>(1)</sup>		18	18	18	12
WATER CONSUMPTION / CYCLE (water pressure 200kPa)		1.8 L			
BOILER CAPACITY		3.8 L			
BOILER HEATING ELEMENT		2800 W			
RINSING TEMPERATURE (SET)		85°C			
TANK CAPACITY		6.2 L			
TANK HEATING ELEMENT		1100 W			
TANK TEMPERATURE (SET)		55°C			
PUMP POWER		250 W (150 L/min <sup>***</sup> )			
DRAIN PUMP (optional)		25 W h max draining 0.8 m (40 L/min <sup>***</sup> )			
NOISE		59.9±0.7 dB(A)			

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

(<sup>1</sup>) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.