



	WATER CONNECTION 3/4" GAS
	DRAIN PIPE Ø 24mm
	ELECTRICAL SUPPLY

TECHNICAL DATA				
EXTERNAL DIMENSIONS				
width	600 mm			
depth	680 mm			
height	860 mm			
WEIGHT	67.5 kg			
VOLTAGE	400V 3N 50Hz			
POWER REQUIRED	6650 W			
WATER HARDNESS	2-8 °F			
INLET WATER PRESSURE	200-400 kPa			
CROCKERY DIMENSIONS				
plates diameter	400 mm			
dishes max. height	400 mm/EURONORM			
RACK DIMENSION	500X500 mm			
RACK EQUIPMENT	1XC40 - 1XC44 - 1X15060			
WASHING CYCLES (sec)	1 (60)	2 (120)	3 (180)	4 (300)
WATER SUPPLY 55°C				
racks/h(*) <sup>(1)</sup>	60	30	20	12
WATER SUPPLY 10°C				
racks/h(*) <sup>(1)</sup>	25	25	20	12
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	2.3 l			
BOILER CAPACITY	5.7 l			
BOILER HEATING ELEMENT	6000 W			
RINSING TEMPERATURE (SET)	85°C			
TANK CAPACITY	16.5 l			
TANK HEATING ELEMENT	2700 W			
TANK TEMPERATURE (SET)	55°C			
PUMP POWER	650 W (340 l/min***)			
DRAIN PUMP (optional)	25 W h MAX draining 0.8 m (40 l/min***)			
NOISE	61,3±0.7 dB(A)			

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

<sup>(1)</sup> In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.