



	WATER CONNECTION 3/4" GAS
	DRAINING Ø 24mm
	ELECTRICAL SUPPLY

TECHNICAL DATA					
EXTERNAL DIMENSIONS					
width		600 mm			
depth		610 mm			
height		850 mm			
WEIGHT(basic version)		64.5 kg			
VOLTAGE		400V 3N 50Hz			
POWER REQUIRED		6650 W			
WATER HARDNESS		2-8 °F			
INLET WATER PRESSURE		200-400 kPa			
CROCKERY DIMENSIONS					
plates diameter		340 mm			
size allowed		325 mm/GASTRONORM			
RACK DIMENSIONS		500X500 mm			
RACK EQUIPMENT		1XC40 - 1XC44 - 1X15060			
WASHING CYCLES	(sec)	1 (60)	2 (120)	3 (180)	4 (300)
WATER SUPPLY 55°C					
racks/h(*) ⁽¹⁾		55	30	20	12
WATER SUPPLY 10°C					
racks/h(*) ⁽¹⁾		23	23	20	12
WATER CONSUMPTION / CYCLE		2.6 l			
BOILER CAPACITY		8.2 l			
BOILER HEATING ELEMENT		6000 W			
RINSING TEMPERATURE (SET)		85°C			
TANK CAPACITY		16.5 l			
TANK HEATING ELEMENT		2700 W			
TANK TEMPERATURE (SET)		55°C			
PUMP POWER		650 W (340 l/min***)			
DRAIN PUMP (optional)		25 W h MAX draining 0.8 m (40 l/min***)			
NOISE		61,3±0.7 dB(A)			

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.